

COMBINATIETABEL



MU3R19

Koelen														
Aantal units	Combinatie van binnendeel (kBtu/u)					Totale capaciteit						Opgenomen vermogen (W)		
						Min		Nominaal		Max		Min	Nom	Max
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Totaal	Btu/u	kW	Btu/u	kW	Btu/u	kW	Min	Nom	Max
1 UNIT	5				5	3,600	1.06	5,000	1.47	6000	1.76	288	363	571
	7				7	4,200	1.23	7,000	2.05	8400	2.46	319	478	645
	9				9	5,400	1.58	9,000	2.64	10800	3.17	378	595	847
	12				12	7,200	2.11	12,000	3.52	14400	4.22	478	822	1139
	15				15	8,520	2.50	15,000	4.40	17040	4.99	573	1003	1356
	18				18	10,800	3.17	18,000	5.28	21600	6.33	747	1302	1827
2 UNIT	5	5			10	7,200	2.11	10,000	2.93	12000	3.52	350	532	788
	5	7			12	7,200	2.11	12,000	3.52	14400	4.22	350	669	991
	5	9			14	8,400	2.46	14,000	4.10	16800	4.92	408	821	1215
	7	7			14	8,400	2.46	14,000	4.10	16800	4.92	408	821	1215
	7	9			16	9,600	2.81	16,000	4.69	19200	5.63	469	991	1467
	5	12			17	10,200	2.99	17,000	4.98	20400	5.98	532	1083	1603
	9	9			18	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	7	12			19	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	5	15			20	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	9	12			21	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	7	15			22	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	5	18			23	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	9	15			24	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	12	12			24	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	7	18			25	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	9	18			27	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	12	15			27	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	5	24			29	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	12	18			30	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
	15	15			30	10,800	3.17	18,000	5.28	21600	6.33	599	1182	2040
3 UNIT	5	5	5		15	9,000	2.64	15,000	4.40	18000	5.28	422	837	1239
	5	5	7		17	10,200	2.99	17,000	4.98	20400	5.98	481	1013	1500
	5	5	9		19	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	7	7		19	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	7	9		21	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	7	7		21	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	5	12		22	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	9	9		23	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	7	9		23	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	7	12		24	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	5	15		25	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	9	9		25	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	9	12		26	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	7	12		26	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	7	15		27	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	9	9	9		27	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	9	12		28	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	5	18		28	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	9	15		29	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	12	12		29	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	7	7	15		29	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	5	7	18		30	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918
	9	9	12		30	10,800	3.17	18,000	5.28	21600	6.33	544	1111	1918

※ Vanwege ons innovatiebeleid is het mogelijk dat bepaalde specificaties zonder kennisgeving worden gewijzigd.

COMBINATIETABEL



Verwarmen														
Aantal units	Combinatie van binnendeel (kBtu/u)					Totale capaciteit						Opgenomen vermogen (W)		
						Min		Nominaal		Max				
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Totaal	Btu/u	kW	Btu/u	kW	Btu/u	kW	Min	Nom	Max
1 UNIT	5				5	4,000	1.17	5,500	1.61	6325	1.85	279	384	589
	7				7	5,040	1.48	8,400	2.46	9660	2.83	342	579	743
	9				9	6,480	1.90	10,800	3.17	12420	3.64	483	757	997
	12				12	7,920	2.32	13,200	3.87	15180	4.45	537	954	1234
	15				15	9,900	2.90	16,500	4.84	18975	5.56	688	1189	1593
	18				18	11,880	3.48	19,800	5.80	22770	6.67	845	1483	1978
2 UNIT	5	5			10	7,200	2.11	12,000	3.52	14400	4.22	329	598	861
	5	7			12	8,640	2.53	14,400	4.22	17280	5.06	430	904	1301
	5	9			14	10,080	2.95	16,800	4.92	20160	5.91	484	945	1360
	7	7			14	10,080	2.95	16,800	4.92	20160	5.91	484	945	1360
	7	9			16	11,520	3.38	19,200	5.63	23040	6.75	540	1118	1610
	5	12			17	12,240	3.59	20,400	5.98	24480	7.17	598	1319	1899
	9	9			18	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	7	12			19	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	5	15			20	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	9	12			21	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	7	15			22	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	5	18			23	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	9	15			24	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	12	12			24	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	7	18			25	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	9	18			27	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	12	15			27	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	5	24			29	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	12	18			30	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
	15	15			30	12,960	3.80	21,600	6.33	25000	7.33	660	1391	2040
3 UNIT	5	5	5		15	10,800	3.17	18,000	5.28	21600	6.33	497	946	1363
	5	5	7		17	12,240	3.59	20,400	5.98	24480	7.17	551	1118	1610
	5	5	9		19	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	7	7		19	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	7	9		21	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	7	7		21	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	5	12		22	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	9	9		23	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	7	9		23	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	7	12		24	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	5	15		25	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	9	9		25	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	9	12		26	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	7	12		26	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	7	15		27	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	9	9	9		27	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	9	12		28	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	5	18		28	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	9	15		29	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	12	12		29	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	7	7	15		29	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	5	7	18		30	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823
	9	9	12		30	12,960	3.80	21,600	6.33	25000	7.33	725	1266	1823